

## Dynacom DZ6025N SERIES 25CH 960P/16CH 1080P 9HDD NVR



<b>Model Number</b>	Dynacom DZ6025N	
<b>Operating System</b>	Embedded LINUX operating system	
<b>Image Code Control</b>	Image code quality adjustable, variable bitstream and constant bitstream optional	
<b>Dual Stream</b>	Each channel can set main stream and sub stream	
<b>Video Standard</b>	1080P(1920×1080)30fps / 960P(1280×960) 30fps / 720P(1280×720)30fps	
<b>Monitoring Image Quality</b>	1080P(1920×1080) / 960P(1280×960) / 720P(1280×720)	
<b>Backup Way</b>	Support U disk, USB mobile HDD, USB DVD-RW, network storage and backup (Partly needs IPC Support)	
<b>Operation Way</b>	Mouse	
<b>Local Login</b>	User name and password	
<b>Recording Storage</b>	Local HDD, network	
<b>External Ports</b>	<b>Video Input</b>	① 25×(1280*960)+sub[720*576]+4Ref.+9Play 25ch 1.3MP IP Camera ② 16×1920*1080)+sub[720*576]+4Ref.+4Play 16ch 2.0MP IP Camera ③ 8×(2048*1536)+sub[960*576]+4Ref.+4Play 8ch 3.0MP IP Camera ④ 4×(2592*1944)+sub[960*576]+4Ref.+4Play 4ch 1.3MP IP Camera
	<b>Wireless Port</b>	3G, WIFI
<b>HDD</b>	<b>HDD Port</b>	9 SATA+1 E-SATA HDD ports
	<b>MAX Capacity</b>	Each port supports MAX 4TB HDD
<b>Mobile Surveillance</b>	Support( iPhone, Windows Mobile, BlackBerry, Symbian, Android) smart phone	
<b>Power Supply</b>	ATX110-220V 300W 50-60Hz	
<b>Power Consumption</b>	≤30W (without HDD)	
<b>Working Temperature</b>	-10°C~ +55°C	
<b>Working Humidity</b>	10%-90%	
<b>Dimension</b>	Equipment: 440mm×450mm×90mm, Packing: 539mm×550mm×225mm	
<b>Weight(without HDD)</b>	N.W.: 7.4Kg; with packing: 10Kg	
<b>Outside Carton</b>	2pcs/carton. 555mm×545mm×470mm; weight: 21Kg	

