

SW3009-8ET-P96

8-Port Fast Ethernet PoE Switch



Features

- Layer two commercial switch
- Supports IEEE802.3, IEEE802.3u and IEEE802.3X standards
- MAC auto learning, aging, MAC address capacity is 2K
- Supports MDI/MDIX self-adaptation
- Support PoE, PoE+, Hi-PoE
- Adopts metal enclosure

Product Overview

DH-PFS3009-8P-96 is an 8-port fast Ethernet switch, which supports 250 meters long distance PoE transmission. It provides 8*10/100Mbps PoE ports and 1*100 Mbps uplink port. The product is equipped with two transmission modes (Default/Extend), which are controlled by DIP switch.

Technical Specification

Model	DH-PFS3009-8ET-96
Ethernet Port	1*10/100 Base-T 8*10/100 Base-T (PoE power supply)
PoE Power Consumption	Port1≤60W, Port2-8≤30W, Totals≤96W
PoE Protocol	IEEE802.3af (PoE), IEEE802.3at (PoE+), Hi-PoE
Switching Capacity	1.8Gbps
Packet Forwarding Rate	1.34Mpps
Packet Buffer Memory	768K
MAC Table Size	2K
Flow Control	Enable by default
Application Humidity	10%~90%
Power	DC48~57V power adapter
Lightning Protection	Common Mode 2KV Differential Mode 0.5KV
Working Temperature	-10°C~+55°C
Weight	0.48kg
Dimension(W×D×H)	190mm×100mm×30mm