

# Brickcom

## 3 Megapixel Outdoor Bullet Network Camera

OB-300Af

Cost Effective / High Resolution



- Most Intelligent, Compact and Affordable 3M Outdoor Bullet Camera
- Cost Effective/ High Resolution/ Full Features Camera
- HDTV Quality (Full HD 1080p @ 30fps Streaming)
- Intelligent Multi-Profile Sensor Management® for Different Environments
- Removable IR-cut Filter /Auto Light Sensor for Day and Night
- Unique Design for Low Lux Application (1/2.5" Sensor)
- Built-in Micro SD/SDHC Memory Card Slot for Local Storage
- IP66 Outdoor Enclosure
- 1 DI/DO for External Alarm and Sensor Device
- Power over Ethernet





ONVIF

### Photo Indication & Dimension Diagram



- |  |                   |
|--|-------------------|
| ① IR LED   | ⑧ Digital Input   |
| ② LENS   | ⑨ Digital Output  |
| ③ Light Sensor                                     | ⑩ RS485+          |
| ④ RJ45 Connector 1 (For Ethernet and PoE 802.3 af) | ⑪ RS485-          |
| ⑤ Power Connector (DC12V)                          | ⑫ Line In         |
| ⑥ Ground   | ⑬ Line In Ground  |
| ⑦ power+5V   | ⑭ Line out        |
|  | ⑮ Line Out Ground |




## Camera

<b>Hardware System</b>	CPU: 533 MHz Flash: 32M RAM: 256M DDR
<b>Image Sensor</b>	Sensor Type : 1/2.5" CMOS Sensor Sensor Resolution : 2048x1536 pixel
<b>IR Illuminators</b>	Built -In IR Illuminators, effective up to 20 meters IR LED: 35pcs
<b>Day and Night</b>	Removable IR-cut Filter /Auto Light Sensor for Day and Night
<b>Local Storage</b>	Built-in Micro SD/SDHC/SDXC Max.64G Memory Card Slot

## Video

<b>Compression Streaming</b>	H.264 / MPEG4 / MJPEG Simultaneous multiple streams
<b>Video Setting</b>	Multi-Profile Sensor Management Day/ Night / Sunset/ User 1/ User 2 Auto Exposure / Gain / White Balance Control Manual Exposure Control:1/20000~1/5s Manual Gain Control: 1X~32X Manual White Balance Control: 2000K~7000K
<b>S/N Ratio</b>	38.1dB
<b>Image Resolution</b>	<b>3M</b> : 2048x1536 @ 18fps <b>2M (1080p Full HD)</b> : 1920x1080 @ 30fps <b>1M (720p HDTV)</b> : 1280x720 @ 30fps

## Product Distinction

OB-300Af-D  Lens Type  
 1. 4mm, F=1.6  
 2. 6mm, F=1.6  
 3. 8mm, F=1.6

## Events and Alarm Management

<b>Events</b>	Motion Detection Digital Input Schedule Audio Detection
<b>Alarm</b>	Stream/Snapshot to FTP/Email/Samba/SD-Card Activate Digital Output HTTP/Email Notification Audio Notification

## Audio

<b>Audio Streaming</b>	2-way Audio Support
<b>Audio Compression</b>	G.711, AMR (8 kHz, Mono, PCM)
<b>Audio Input/ Output</b>	Line in/ Line out

## General

<b>Communication</b>	Ethernet : one 10/100Mbps RJ-45 Supported Protocols : TCP/IP, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, FTP, HTTP, Samba, PPPoE, UPnP, RTP, RTSP, RTCP, IPv6
<b>Power Input</b>	DC12V/ 1A(Power Supply)/ PoE 802.3af
<b>Max. Power Consumption</b>	8 watts
<b>Environment</b>	Operating Temperature: -20°C ~ 50°C(-4°F ~122°F) Operating Humidity : 10% ~ 80%
<b>Dimension</b>	282 (L) 81 (W) X 152.5 (H) mm
<b>Weight</b>	Net: 855g/1.89lb
<b>Housing</b>	Weather-proof IP66
<b>Certification</b>	FCC, CE
<b>Viewing System Requirements</b>	OS: Microsoft Windows 7/Vista/XP/2000 Browser: Mozilla Firefox, Internet Explorer 6/7 or above, Safari, Google Chrome Cell Phone: 3GPP player Real Player: 10.5 or above Quick Time: 6.6 or above VLC
<b>Warranty</b>	Limited One-year warranty

OB-300Af	f=4mm	f=6mm	f=8mm
Lens Type	Board Lens	Board Lens	Board Lens
F Number	F=1.6	F=1.6	F=1.6
Minimum Illumination	0 lux (IR ON, B/W) 0.1lux (IR OFF, B/W) 0.2 lux (F1.6, Color)	0 lux (IR ON, B/W) 0.12lux (IR ON, B/W) 0.22 lux (F1.6, Color)	0 lux (IR ON, B/W) 0.25lux (IR ON, B/W) 0.35 lux (F1.6, Color)
FOV(H/V/D)	66°/49°/85°	43°/32°/53°	32°/23°/40°

## Work Best With

### Network Equipment Options



**POE 16U**  
PoE Injector



**PS-588I**  
8-port 10/100M PoE Fast Ethernet Switch



**PS-7242IL-AF**  
24-port 10/100M PoE Web Smart Ethernet Switch