

Full HD in tough environments

3 Megapixel Network Camera



3Megapixel Full HD Network Vandal-Resistant IR Dome Camera

SNV-7080R

The SNV-7080R is an ONVIF compliant vandal-resistant dome camera from Samsung's 3 Megapixel camera range. It utilizes Samsung's WiseNet2 DSP chipset which has been specifically designed to provide users with maximum benefit from the latest megapixel camera technology. The IP66 rated SNV-7080R can work effectively in more demanding environments that are prone to severe or varying weather conditions as well as tampering or physical attack. In addition, thanks to its built-in 15 IR LEDs, the SNV-7080R has the ability to capture clear images of objects which are up to 75ft from the camera, even when the area is in total darkness. Capable of displaying multiple resolutions from CIF (320 x 240) through to 16:9 format 1080p full HD and up to full 3 megapixel (2048 x 1536), these resolutions have the ability to be transmitted simultaneously, allowing the most relevant stream to be transmitted to your viewing or recording device.



- 3 ~ 8.5mm (2.8x) motorized vari-focal lens
- Max. 3M (2048 x 1536) resolution
- 16 : 9 Full HD (1080p) display support
- Built-in IR LED (15ea), viewable length of 75ft
- H.264 / MJPEG dual codec and multiple streaming
- Smart Compression (ROI encoding)
- IP66 Grade (outdoor rated)

3Megapixel Full HD Network Vandal-Resistant IR Dome Camera

SNV-7080R



Specifications




SNV-7080RN/P

VIDEO	
Imaging Device	1/2.8" 3M PS CMOS
Total Pixels	2,144(H) X 1,588(V)
Effective Pixels	2,096(H) X 1,561(V)
Scanning System	Progressive
Min. Illumination	Color : 1Lux (F1.2, 50IRE), 0.017Lux (Sens up 60x), B/W : 0Lux (F1.2, 50IRE, IR LED On)
S / N Ratio	50dB
Video Output	CVBS : 1.0 Vp-p / 75Ω composite, 704x480(N), 704x576(P), for installation
LENS	
Focal Length (Zoom Ratio)	3~8.5mm (2.8x) Motorized Vari-focal
Max. Aperture Ratio	F1.2
Angular Field of View	H : 100°(Wide) ~ 35.3°(Tele), V : 74.6°(Wide) ~ 26°(Tele)
Focus Control	Remote control via network (Manual, One-shot AF)
Lens Type	DC Auto Iris
Mount Type	Board-in type
PAN / TILT / ROTATE	
Pan Range	0° ~ 355°
Tilt Range	0° ~ 90°
Rotate Range	0° ~ 355°
OPERATIONAL	
IR LED	15 ea
Viewable Length	75ft
Camera Title	Off / On (Displayed up to 15 characters)
Day & Night	Auto (ICR) / Color / B/W
Backlight Compensation	Off / BLC / HLC
Wide Dynamic Range	Off / On (Full HD WDR)
Contrast Enhancement	SSDR (Samsung Super Dynamic Range) (Off / On)
Digital Noise Reduction	SSNRIII (2D+3D Noise filter) (Off / On)
Motion Detection	Off / On (4 programmable zones)
Privacy Masking	Off / On (1ea 4 Point Polygonal + 16ea Rectangular zones)
Sens-up (Frame Integration)	Off / Auto (2X ~ 60X)
Gain Control	Off / Low / Medium / High
White Balance	ATW / AWC / Manual / Indoor / Outdoor
Electronic Shutter Speed	Auto / A.FLK / Manual
Flip / Mirror	Off / On
Intelligent Video Analytics	Scene Change, Virtual Line, Enter / Exit, Appear / Disappear
Alarm I/O	Input 1ea / Output 1ea (Relay)
NETWORK	
Ethernet	RJ-45 (10/100BASE-T)
Video Compression Format	H.264, M-JPEG <3M Mode> 2048 x 1536, 1920 x 1080P (Full HD), 1600 x 1200, 1280 x 1024, 1280 x 960, 1280 x 720P(HD), 1024 x 768, 800 x 600, 800 x 450, 640 x 480, 640 x 360, 320 x 240, 320 x 180 <2M Mode> 1920 x 1080P (Full HD), 1280 x 1024, 1280 x 960, 1280 x 720P(HD), 1024 x 768, 800 x 600, 800 x 450, 640 x 480, 640 x 360, 320 x 240, 320 x 180 <3M Mode> * H.264 : Max 20fps at all resolutions * MJPEG : 800 x 600 ~ 320 x 180 - 20 fps, 1280 x 1024 ~ 1920 x 1080 - 15 fps, 2048 x 1536 - 10 fps <2M Mode> * H.264 : Max 30fps at all resolutions (When WDR ON, Max. framerate is Max 15fps.) * MJPEG : 800 x 600 ~ 320 x 180 - 30 fps, 1280 x 1024 ~ 1920 x 1080 : 15 fps
Resolution	
Max. Framerate	
Smart Codec	Yes (Area Based Method, Face Detection Method)
Video Quality Adjustment	H.264 : Compression Level, Target Bitrate Level Control, M-JPEG : Quality Level Control
Bitrate Control Method	H.264 : CBR or VBR, M-JPEG : VBR
Streaming Capability	Multiple Streaming (Up to 6 Profiles)
Audio I/O	Mic/Line in , Line out
Audio Compression Format	G.711 u-law
Audio Communication	Bi-directional
IP	IPv4, IPv6
Protocol	TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTSP, NTP, HTTP, HTTPS, SSL, DHCP, PPPOE, FTP, SMTP, ICMP, IGMP, SNMPV1/V2C/V3(MIB-2), ARP, DNS, DDNS
Security	HTTPS(SSL) Login Authentication, Digest Login Authentication, IP Address Filtering User access Log, 802.1X Authentication
Streaming Method	Unicast / Multicast
Max. User Access	10 users at Unicast Mode
Memory Slot	SD/SDHC
ONVIF Conformance	Yes
Webpage Language	English, French, German, Spanish, Italian, Chinese, Korean, Russian, Japanese, Swedish, Danish, Portuguese, Turkish, Polish, Czech, Rumanian, Serbian, Dutch, Croatia, Hungary, Greek
Web Viewer	Supported OS : Windows XP / VISTA / 7, MAC OS, Supported Browser : Internet Explorer 6.0 or Higher, Firefox, Google Chrome, Apple Safari
Central Management Software	NET-I viewer
ENVIRONMENTAL	
Operating Temperature / Humidity	-40°C ~ +50°C (-40°F ~ +122°F) / ~ up to 100%
Ingress Protection	IP66 Grade (Waterproof)
ELECTRICAL	
Input Voltage / Current	12V DC, 24V AC, PoE (IEEE802.3af)
Power Consumption	Max. 6W (DC 12V), Max. 7W (AC 24V, PoE (DC 48V)), Max. 11W (AC24V - Heater On); Heaters work on 24VAC only
MECHANICAL	
Color / Material	Body : Ivory / Aluminum
Dimensions (WxH)	Ø160 x 134.5mm (Ø6.3" x 5.3")
Weight	1.4Kg (3.09 lb)

Dimensions

Unit : mm (inch)



Accessories (Optional)



■ DISTRIBUTED BY

