

## DS-6101HFI-IP Digital Video Server



### Key Features

- High performance DSP hardware compression
- H.264 video compression
- Dual streams
- Support variable bit rate and frame rate
- Embedded Linux OS

### Specifications

		DS-6101HFI-IP
Video/Audio input	Video compression	H.264
	Video input	1-ch
	Video input interface	BNC (1.0Vp-p, 75Ω)
	Audio compression	OggVorbis, 16Kbps
	Audio input	1-ch
	Audio input interface	BNC(2Vp-p, 1kΩ)
Video/Audio output	Voice talk input	1, RCA 2.0Vp-p, 1kΩ
	Encode/Decode resolution	4CIF/DCIF/2CIF/CIF/QCIF
	Frame rate	4CIF: 25(P)/30(N) fps
	Stream type	Video/Video&Audio
	Support dual stream	Yes
	Video bit rate	32Kbps ~ 2Mbps, or user-defined (Max. 8Mbps)
External interface	Audio output	1 Channel RCA (Linear Electrical Level, 600Ω)
	Network interface	1 RJ45 10M/100M adaptive Ethernet interface
	RS-232 Port	1 RJ45 RS-232 Port
	RJ-485 port	1 (T+, T-)
	Alarm input	1-ch
	Alarm output	1-ch
General	Power supply	12VDC
	Consumption	≤12W
	Working temperature	-10°C~+55°C(14°F~131°F)
	Working humidity	10%~90%
	Dimension	120(D)x70(W)x45mm(H)(4.73"(D)x2.76"(W)x1.77"(H))
	Weight(without HDD)	≤500g(1.10lbs)