

DS-7000HUHI-K1 SERIES TURBO HD DVR

Features and Functions

Video Input and Transmission

- Self-adaptive HDTV/HD/SD/TVI/AHD/TVBS signal input
- Up to 2-ch 6 MP IP cameras input
- 5 MP/4 MP HDTV video input and live view
- Defogging function enabled for the supported analog cameras
- Long distance transmission over UTP and coaxial cable: max. 800m for 1080p and 1200m for 720p HDTV signal

Compression and Recording

- H.265+/H.265/H.264+/H.264 encoding for the main stream, and H.265/H.264 for the sub-stream of analog cameras
- Connectable to H.265+/H.265/H.264+/H.264 IP cameras
- H.265+ can be enabled to improve encoding efficiency and reduce data storage costs
- Full channel recording at up to 5 MP resolution

Video Output

- Simultaneous HDMI/VGA output
- HDMI output at up to 4K (3840 × 2160) resolution for DS-7008HUHI-K1
- Separate CVBS output

Storage and Playback

- 1 SATA interface (up to 8 TB capacity per HDD)
- 4/8-ch synchronous playback
- Smart search for efficient playback
- Supports the 3rd party cloud storage (Dropbox/Google Drive/Microsoft OneDrive)

Smart Function

- Supports multiple VCA (Video Content Analytics) events for both analog and smart IP cameras
- Supports line crossing detection and intrusion detection of all channels, and 2-ch sudden scene change detection
- VCA information overlay in live view and smart playback
- VQD (Video Quality Diagnostics)
- Supports PTZ control via Omnicast VMS of Genetec protocol

Network & Ethernet Access


- Hik-Connect & DDNS (Dynamic Domain Name System) for easy network management
- 1 RJ45 10M/100M self-adaptive Ethernet interface for DS-7004HUHI-K1, and 1 RJ45 10M/100M/1000M self-adaptive Ethernet interface for DS-7008HUHI-K1
- Output bandwidth limit configurable



Specifications

| Model | DS-7004HUHI-K1 | | DS-7008HUHI-K1 | | |
|----------------------|---|--|---|---|--|
| Video/Audio input | Video compression | H.265+/H.265/H.264+/H.264 | | | |
| | Analog video input | 4-ch | 8-ch | | |
| | | BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection | | | |
| | HDTVI input | 5 MP, 4 MP, 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25 | | | |
| | AHD input | 1080p25, 1080p30, 720p25, 720p30 | | | |
| | HDCVI input | 1080p25, 1080p30, 720p25, 720p30 | | | |
| | CVBS input | PAL/NTSC | | | |
| | IP video input | 2-ch | | | |
| | | Up to 6 MP resolution | | | |
| | | Supports H.265+/H.265/H.264+/H.264 IP cameras | | | |
| Audio compression | G.711u | | | | |
| Audio input | 4-ch, RCA (2.0 Vp-p, 1 KΩ) | | | | |
| CVBS output | 1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480 | | | | |
| Video/Audio output | HDMI/VGA output | 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz | | VGA: 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz HDMI: 1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz | |
| | | Encoding resolution | | | 5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF |
| | Frame rate | Main stream: 5 MP@12fps/4 MP@15fps/3 MP@18fps 1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) Sub-stream: WD1/4CIF/CIF@25fps (P)/30fps (N) | | | |
| | Video bit rate | 32 Kbps to 10 Mbps | | | |
| | Audio output | 1-ch, RCA (Linear, 1 KΩ) | | | |
| | Audio bit rate | 64 Kbps | | | |
| | Dual stream | Support | | | |
| | Stream type | Video, Video & Audio | | | |
| | Synchronous playback | 4-ch | | 8-ch | |
| | | | | | |
| Network management | Remote connections | 128 | | | |
| | Network protocols | TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF | | | |
| Hard disk | SATA | 1 SATA interface | | | |
| | Capacity | Up to 8 TB capacity for each disk | | | |
| External interface | Two-way audio input | 1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the 1 st audio input) | | | |
| | Network interface | 1, RJ45 10M/100M self-adaptive Ethernet interface | 1, RJ45 10M/100M/1000M self-adaptive Ethernet interface | | |
| | USB interface | 2 × USB 2.0 | Front panel: 1 × USB 2.0 Rear panel: 1 × USB 3.0 | | |
| | Serial interface | RS-485 (half-duplex) | | | |
| General | Power supply | 12 VDC | | | |
| | Consumption (without HDD) | ≤ 10 W | ≤ 20 W | | |
| | Working temperature | -10 °C to +55 °C (+14 °F to +131 °F) | | | |
| | Working humidity | 10% to 90% | | | |
| | Dimensions (W × D × H) | 315 × 242 × 45 mm (12.4 × 9.5 × 1.8 inch) | | | |
| Weight (without HDD) | ≤ 1.16 kg (2.6 lb) | ≤ 2 kg (4.4 lb) | | | |

Physical Interfaces



NOTE

The rear panel of DS-7008HUHI-K1 provides 8 video input interfaces.

| Index | Description | Index | Description |
|-------|--------------------------|-------|-------------------------|
| 1 | VIDEO IN | 8 | RS-485 Serial Interface |
| 2 | AUDIO IN, RCA Connector | 9 | 12 VDC Power Input |
| 3 | AUDIO OUT, RCA Connector | 10 | Power Switch |
| 4 | VGA Interface | 11 | GND |
| 5 | HDMI Interface | 12 | VIDEO OUT |
| 6 | USB Interface | | |
| 7 | LAN Network Interface | | |

Available Models

DS-7004HUHI-K1, DS-7008HUHI-K1

Distributed by



HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Africa
T +27 (0) 0351172
sale.africa@hikvision.com

Hikvision Europe
T +31-23-55-42-770
info.eu@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision Korea
T +82-31-731-8841
sales.korea@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +01628-902140
support.uk@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com