

DS-7W00NI-E1 SERIES NVR



Features and Functions

Video Input and Transmission

- Connectable to the third-party network cameras
- Up to 8 network cameras can be connected

Compression and Recording

- H.264+ compression effectively reduces the storage space and costs by up to 50%
- Full channel recording at up to 4 MP resolution

HD Video Output

- HDMI/VGA output at 1080p resolution

Storage and Playback

- Up to 2-ch synchronous playback at 4 MP resolution or 4-ch at 1080p resolution
- 1 SATA hard disks can be connected with 6TB capacity
- HDD quota and group modes; different capacity can be assigned to different channel

Smart Function

- Supports multiple VCA(Video Content Analytics) events detection
- Smart search for the selected area in the video; and smart playback to improve the playback efficiency
- One-key operation: automatically search, modify and add IP cameras after device is activated

Network & Ethernet Access

- Hik-Connect and DyDDNS for easy network management
- 100 Mbps Ethernet network interface




Specifications

Model		DS-7W04NI-E1	DS-7W08NI-E1
Video/Audio input	IP video input	4-ch	8-ch
	Two-way audio input	1-ch, RCA (2.0 Vp-p, 1kΩ)	
Network	Incoming bandwidth	40 Mbps	60 Mbps
	Outgoing bandwidth	40 Mbps	40 Mbps
	Remote connection	64	
Video/Audio output	Recording resolution	4 MP/3 MP/1080p/1.3 MP/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF	
	Frame rate	50 fps (P)/60 fps (N)	
	HDMI/VGA output	1-ch, resolution: 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	
	Audio output	1-ch, RCA (Linear, 1kΩ)	
Decoding	Live view/Playback resolution	4 MP/3 MP/1080p/1.3 MP/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF	
	Capability	2-ch@4 MP, 4-ch@1080p	
Hard disk	SATA	1 SATA interface for 1 HDD	
	Capacity	Up to 6TB for each disk	
Network management	Network protocols	TCP/IP, DHCP, Hik-Connect, DDNS, NTP, SADP, SMTP, UPnP™	
External interface	Network interface	1 RJ-45 10/100 Mbps self-adaptive Ethernet interface	
	USB interface	2 × USB 2.0	
General	Power supply	12 VDC	
	Consumption (without hard disk)	≤ 18 W	
	Working temperature	-10 °C to +55 °C (14 °F to 131 °F)	
	Working humidity	10 % to 90 %	
	Dimensions (W × D × H)	200 × 205 × 48 mm (7.9" × 8.1" × 1.9")	
	Weight (without hard disk)	≤ 1 kg (2.2 lb)	

Physical Interfaces

DS-7W00NI-E1



Index	Name	Index	Name
1	Power Supply	5	Audio Out
2	Audio In	6	VGA Interface
3	HDMI Interface	7	USB Interface
4	LAN Network Interface	8	Ground

Available Models

DS-7W04NI-E1, DS-7W08NI-E1

Distributed by



HIKVISION

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Africa
T +27 (10) 0351172
sale.africa@hikvision.com

Hikvision Europe
T +31-23-55-42-770
info.eu@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision Korea
T +82-31-731-8841
sales.korea@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +01628-902140
support.uk@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com