



**DS-8000HSI-S Series Net DVR**  
**Technical Manual**

## Notices

---

The information in this documentation is subject to change without notice and does not represent any commitment on behalf of HIKVISION. HIKVISION disclaims any liability whatsoever for incorrect data that may appear in this documentation. The product(s) described in this documentation are furnished subject to a license and may only be used in accordance with the terms and conditions of such license.

Copyright © 2006-2010 by HIKVISION. All rights reserved.

**This documentation is issued in strict confidence and is to be used only for the purposes for which it is supplied.** It may not be reproduced in whole or in part, in any form, or by any means or be used for any other purpose without prior written consent of HIKVISION and then only on the condition that this notice is included in any such reproduction. No information as to the contents or subject matter of this documentation, or any part thereof, or arising directly or indirectly therefrom, shall be given orally or in writing or shall be communicated in any manner whatsoever to any third party being an individual, firm, or company or any employee thereof without the prior written consent of HIKVISION. Use of this product is subject to acceptance of the HIKVISION agreement required to use this product. HIKVISION reserves the right to make changes to its products as circumstances may warrant, without notice.

**This documentation is provided "as-is," without warranty of any kind.**

Please send any comments regarding the documentation to:  
[overseabusiness@hikvision.com](mailto:overseabusiness@hikvision.com)

Find out more about HIKVISION at [www.hikvision.com](http://www.hikvision.com)

# Contents

---

- 1. Overview**
- 2. Model Description**
- 3. Features**
- 4. Specifications**

## 1. Overview

DS-8000HSI-S series Network Digital video Recorder is an excellent digital surveillance product adopts embedded MCU (Microprocessor Control Unit) and an embedded Real-Time Operating System (RTOS), along with the most advanced technology in the Information technology Industry such as video encoding/decoding, hard disk recording and TCP/IP transmission. The firmware is burned into the flash, making it more stable and reliable than software programs running from a standard disk drive.

DS-8000HSI-S series combines the advantages of Digital Video Recorder (DVR) and Digital Video Server (DVS). It is widely applied as a stand-alone unit or a part of a powerful surveillance system.



Front Panel



DS-8004HSI-S Rear Panel



DS-8008HSI-S Rear Panel



**DS-8016HSI-S Rear Panel**

## 2. Model Description

---

**DS-8004HSI-S:** 4-ch video input and 4-ch video loop out. No audio input. Each channel can max support CIF encoding resolution real time. It has 4 SATA interfaces.

**DS-8008HSI-S:** 8-ch video input and 8-ch video loop out. No audio input. Each channel can max support CIF encoding resolution real time. It has 8 SATA interfaces.

**DS-8016HSI-S:** 16-ch video input and 16-ch video loop out. No audio input. Each channel can max support CIF encoding resolution real time. It has 8 SATA interfaces.

**Note: 1. The default DVRs are without HDD or CD-R/W.**

**2. A factory recommended HDD should be used for this device.**

## **3. Features**

---

### **3.1 Compression:**

- Support up to 16 video channels (NTSC/PAL). Each channel is independent with H.264 hardware compression in real time (NTSC 30FPS, PAL 25FPS).
- Support both variable bit rate and frame rate
- Support 4CIF, DCIF, 2CIF, CIF and QCIF resolution.
- Support multi-area motion detection
- Support OSD and changeable OSD position

### **3.2 Local functions:**

#### **3.2.1 Recording:**

- Support multiple recording types, including schedule recording, manual recording, motion detection, external alarm, motion & alarm and motion | alarm, etc.
- Support 8 HDDs. Each HDD can support 2000GB maximum.
- Support FAT32 file system
- Support NAS Recording.
- Support Event Recording Para. Setup.
- Support HDD S.M.A.R.T technology
- Support continuous (overwrite) and linear (stop when full) record modes
- Support backup recorded files and video clips with USB memory stick (thumb drive), USB HDD, USB CD-R/W, USB DVD-R/W or SATA HDD.

#### **3.2.2 Preview and playback:**

- Support BNC analog monitor and VGA output for main output
- Support multiple live view modes
- Support video loop output.
- Support Privacy Mask
- Support view tampering alert.
- Support video signal loss alert.
- Support play forward, backward, pause, frame-by-frame, etc
- Support play back by files or by time/date
- Displays local record status

#### **3.2.3 PTZ:**

- Support multiple PTZ protocols
- Support preset, sequence and cruise

**3.2.4 Alarms:**

- Support exception alarm, motion detection alarm, external alarm, etc

**3.3 Miscellaneous:**

- Support IR Remote control
- Support RS-485 keyboard
- Support multi-level user management
- Support Mouse Operation Menu.
- Support multiple upgrade modes, including FTP, USB and CD.

**3.4 Network:**

- Support Advanced Network Function: NTP, DDNS and E-mail.
- Support TCP, UDP, RTP, Multicast for network viewing
- Support PPPoE for broad band dialup
- Support PSTN for standard dialup
- Support remote parameters setup
- Alarm information can be sent to remote center
- Network control PTZ
- Network download and playback recorded files from the DVR
- RS-232 supports transparent channel function
- Support IE preview and configuration
- Support SADP protocol
- Support remote log query

**3.5 Development support:**

- Provide network SDK (Software Development Kit)
- Provide client demo source code



## 4. Specifications

Model	DS-8004HSI-S	DS-8008HSI-S	DS-8016HSI-S
Video standard	H.264		
Preview resolution	4CIF (PAL: 704*576, NTSC: 704*480)		
Playback resolution (PAL/NTSC)	4CIF/DCIF/2CIF/CIF/QCIF	2CIF/CIF/QCIF	
Video input	4	8	16
Video input interface	BNC (1.0Vp-p, 75Ω)		
Video loop output	4	8	16
Video output	1 channel, BNC (1.0Vp-p, 75Ω)		
Frame rate (per channel)	4CIF: 8fps DCIF: 8fps 2CIF: 15fps CIF: 25(P)/30(N) fps	2CIF: 8fps CIF: 25(P)/30(N) fps	
Stream type	Video		
Bit rate	32Kbps~2Mbps, user-defined (Max. 8Mbps)		
Communication interface	1 RJ45 10M/100M Adaptive Ethernet Interface		
RS-232 Port	1 RJ45 RS-232 port		
PTZ control	1 RS-485 port (T+, T-, R+, R-)		
Keyboard interface	2 RJ45 ports	1 port (D+, D-)	
SATA interface	4	8	
E-SATA (optional)	1 <sup>st</sup> internal SATA interface can be extended to be E-SATA		
USB interface	1 USB interface, can support USB disk, USB HDD, USB DVD-R/W and CD-R/W		
VGA interface	1 VGA interface, support resolution: 800x600/60Hz, 1024x768/60Hz, 1280*1024/60Hz		
External alarm in	4	16	
Relay output	2	4	
Power supply	100~240VAC, 6.3A, 50~60Hz		
Power consumption	≤70W (without HDD)		

<b>Working temperature</b>	-10°C ~ +55°C
<b>Working humidity</b>	10% ~ 90%
<b>Size</b>	470mm(D)*441mm(W)*90mm(H)
<b>Weight</b>	≤8Kg (without HDD)

PAL: 176×144(QCIF), 352×288(CIF), 704×288(2CIF), 528×384(DCIF), 704×576(4CIF);  
NTSC: 176×120(QCIF), 352×240(CIF), 704×240(2CIF), 528×320(DCIF), 704×480(4CIF).