

DH-IPC-HDPW5442G-Z

4MP WDR IR Dome AI Network Camera



Dahua AI series products adopt the most advanced AI technologies, including deep learning algorithms that primarily target people and vehicles, which provides higher flexibility and accuracy for end-users. This enables the Dahua AI series to offer various advanced applications such as Face Recognition, ANPR, Metadata, People Counting, traffic data statistics, etc. The complete lineup of Dahua AI includes network (PTZ) cameras, network video recorders, servers, and platform management products. Beyond seeing the world, the power of AI allows devices to perceive the environment and understand the world in a better way.

System Overview

Pro AI series contains Face Capture, Perimeter Protection and People Counting functions. Powered by deep-learning Artificial Intelligence algorithms, significantly improved accuracy. Meanwhile, the series features starlight and smart IR technology.

Functions

Face Capture

Face capture is a software application that automatically captures faces from within a digital image or a video frame from a video source. Dahua cameras use advanced deep learning algorithms and are trained by a large number of face data sources, enabling the camera to locate faces quickly and accurately from the video source and capture facial images.

Face Attributes

Through the use of deep learning algorithms to analyze facial images, Dahua cameras can extract six facial attributes from each frame, including Age, Gender, Expression (Jolly/Surprise/Normal/Rage/Sad/Disgusted/Confused/Frightened), Glasses, Mouth Mask, Moustache & Beard. Customers can acquire data of interest via face attributes statistics.

Perimeter Protection

Dahua's Perimeter Protection functions significantly improved accuracy. Perimeter Protection reduces false alarms and decreases pixel count requirements for object detection. Perimeter Protection features custom tripwires based on object type for automation in limited access areas such as pedestrian or vehicle-only zones. This combination of advanced AI analytics and real-time alerts to a desktop or to a mobile client reduces system requirements and resources resulting in greater

- 1/1.8" 4Megapixel progressive scan CMOS
- H.265&H.264 triple-stream encoding
- 25/30fps@2688×1520
- WDR(120dB), Day/Night(ICR), 3D DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 2.7mm~12mm motorized lens
- 1/1 Alarm in/out, 1/1 audio in/out
- Max. IR LEDs Length 45m
- Micro SD memory



surveillance system efficiency.

People Counting

People Counting function uses advanced image processing technology to capture depth information from within images. The camera pairs this information with deep learning algorithms to analyze and detect human bodies and track target objects in real time. The camera provides statistics for separate individuals' entrance and exit with up to 95% counting accuracy.

Metadata

Metadata is feature attribute information extracted from a target object which can be used for data retrieval. Dahua face detection camera can extract six facial attributes and output the metadata for analysis.

Technical Specification

Camera

| | |
|--------------------------|--|
| Image Sensor | 1/1.8" 4Megapixel progressive scan CMOS |
| Effective Pixels | 2688(H) x 1520(V) |
| RAM/ROM | 1G/128MB |
| Scanning System | Progressive |
| Electronic Shutter Speed | Auto/Manual, 1/3~1/100000s |
| Minimum Illumination | 0.0024Lux/F1.8 (Color,1/3s,30IRE) 0.059Lux/F1.8(Color,1/30s,30IRE) 0Lux/F1.8 (IR on) |
| IR Distance | Distance up to 45m (148ft) |
| IR On/Off Control | Auto/ Manual |
| IR LEDs | 3 |

Lens

| | | | | | |
|----------------------|------------------------|-------------|------------|-----------|-----------|
| Lens Type | Motorized | | | | |
| Mount Type | Board-in | | | | |
| Focal Length | 2.7mm~12mm | | | | |
| Max. Aperture | F1.8 | | | | |
| Angle of View | H: 114°~47°, V:62°~26° | | | | |
| Optical Zoom | 4.4x | | | | |
| Aperture Type | Auto | | | | |
| Close Focus Distance | 1.2m(3.94ft) | | | | |
| DORI Distance | Lens | Detect | Observe | Recognize | Identify |
| | W | 56m(184ft) | 20m(66ft) | 9m(30ft) | 4m(13ft) |
| | T | 125m(410ft) | 50m(164ft) | 22m(72ft) | 11m(36ft) |

Pan/Tilt/Rotation

| | |
|-------------------------|--|
| Pan/Tilt/Rotation Range | Pan:0°~355°; Tilt:0°~75°; Rotation:0°~355° |
|-------------------------|--|

Artificial Intelligence

| | |
|----------------------|--|
| Face Capture | Support face image capture |
| Face Attributes | Support 6 kinds of face attributes extraction: Age, Gender, Expression(Jolly/Surprise/Normal/Rage/Sad/Disgusted/Confused/Frightened), Glasses, Mouth Mask, Moustache & Beard |
| Perimeter Protection | Tripwire, Intrusion(Human & Vehicle classification) |
| People Counting | Line crossing people counting, Region people counting, Loitering filter |

General Intelligence

| | |
|----------------------|--|
| Event Trigger | Motion detection, Video tampering, Scene changing, Network disconnection, IP address conflict, Illegal Access, Storage anomaly |
| General Intelligence | Object Abandoned/Missing |

Video

| | |
|----------------------|---|
| Compression | H.265+/H.265/H.264+/H.264/H.264B/H.264H/MJPEG(sub stream) |
| Streaming Capability | 3 Streams |

| | |
|--------------------------------------|--|
| Resolution | 2688x1520/2304x1296/1080P(1920x1080)/1.3M(1280x960)/720P(1280x720)/D1(704x576/704x480)/VGA(640x480)/CIF(352x288/352x240) |
| Frame Rate | Main Stream: 4M(1~25/30fps) |
| | Sub Stream: D1(1~25/30fps) |
| | Third Stream: 1080P(1~11fps) |
| Bit Rate Control | CBR/VBR |
| Bit Rate | H.264: 32~ 8192Kbps H.265: 19~ 8192Kbps |
| Day/Night | Auto(ICR) / Color / B/W |
| BLC Mode | BLC / HLC / WDR(120dB) |
| White Balance | Auto/Natural/Street Lamp/Outdoor/Manual |
| Gain Control | Auto/Manual |
| Noise Reduction | 3D DNR |
| Motion Detetion | Off / On (4 Zone, Rectangle) |
| Region of Interest | Off / On (4 Zone) |
| Electronic Image Stabilization (EIS) | Support |
| Smart IR | Support |
| Defog | Support |
| Digital Zoom | N/A |
| Flip | 0°/90°/180°/270° |
| Mirror | Off / On |
| Privacy Masking | Off / On (4 Area, Rectangle) |

Audio

| | |
|-------------|-----------------------------------|
| Compression | G.711a/ G.711Mu/ AAC/ G.726/G.723 |
|-------------|-----------------------------------|

Network

| | |
|---------------------|---|
| Ethernet | RJ-45 (10/100Base-T) |
| Protocol | HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP;SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; SNMP;QoS; UPnP;NTP |
| Interoperability | ONVIF(Profile S/Profile G), CGI,Milestone,Genetec,P2P |
| Streaming Method | Unicast / Multicast |
| Max. User Access | 20 Users |
| Edge Storage | NAS FTP Mirco SD card 256GB |
| Web Viewer | IE(versions newer than IE8), Chrome, Firefox, Safari(versions newer than Safari 12) |
| Management Software | Smart PSS, DSS, P2P |
| Smart Phone | iOS, Android |

Certifications

| | |
|----------------|--|
| Certifications | CE-LVD:EN60950-1 CE-EMC:Electromagnetic Compatibility Directive 2014/30/EU FCC:47 CFR FCC Part 15, Subpart B |
|----------------|--|

Interface

| | |
|-----------------|--|
| Video Interface | N/A |
| Audio Interface | 1/1 channel In/Out |
| RS485 | N/A |
| Alarm | 1 channel In: 5mA 5VDC 1 channel Out: 300mA 12VDC |

Electrical

| | |
|-------------------|---|
| Power Supply | DC12V(±30%), PoE(802.3af)(Class 0) |
| Power Consumption | DC12V:2.7W 9.9W(IR on) PoE:3.1W 11W(IR on) |

Environmental

| | |
|----------------------|--|
| Operating Conditions | -30° C ~ +60° C (-22° F ~ +140° F) /10%RH~95% RH |
| Storage Conditions | +5° C ~ +40° C (+41° F ~ +104° F) (daily temperature difference within 15° C/59° F) / 10%RH~95% RH |

Construction

| | |
|--------------|--------------------------------|
| Casing | plastic |
| Dimensions | Ø180.5mm×131.4mm (7.11"×5.17") |
| Net Weight | 0.51kg (1.12lb) |
| Gross Weight | 0.73kg (1.61lb) |

Ordering Information

| Type | Part Number | Description |
|------------------------|---------------------|---|
| 4MP camera | DH-IPC-HDPW5442GP-Z | 4MP WDR IR Dome AI Network Camera, PAL |
| | DH-IPC-HDPW5442GN-Z | 4MP WDR IR Dome AI Network Camera, NTSC |
| | IPC-HDPW5442GP-Z | 4MP WDR IR Dome AI Network Camera, PAL |
| | IPC-HDPW5442GN-Z | 4MP WDR IR Dome AI Network Camera, NTSC |
| Accessories (optional) | PFA701 | Junction Box |

Accessories

Optional:





PFA701
Junction Box

In-ceiling Mount

Ceiling Mount

PFA701



Dimensions (mm/inch)

