



DP-12CD1020F-I(2.0MP) IR Mini Bullet Network Camera



Key features

- 1.3MP / 3MP high resolution
- HD real-time video
- 3D DNR & DWDR & BLC
- IR LEDs: up to 30m
- IP66
- PoE
- Compact design
- Bracket included

Dimensions



DP-12CD1020F-I	
Camera	
Image sensor	1/3" progressive scan CMOS
Min. illumination	0.01 lux @F1.2, AGC ON, 0 lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	4mm@ F2.0
	Angle of view: 73.1°(4mm)
Lens mount	M12
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide dynamic range	Digital WDR
Compression Standard	
Video compression	H.264 / MJPEG
H.264 codec profile	Main profile
Bit rate	32 Kbps ~ 12 Mbps
Dual stream	Yes
Image	
Max. Image Resolution	1920 × 1080
Frame rate	50Hz: 25fps (1920 × 1080), 25fps (1280 × 720)
Image settings	Rotate mode, Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes, zone configurable
ROI	Support
Network	
Network storage	Built-in Micro SD/SDHC/SDXC slot, up to 128G, NAS (Support NFS,SMB/CIFS)
Alarm trigger	Line Crossing, Intrusion Detection, Motion detection, Tampering alarm, Storage exception
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
System compatibility	ONVIF, PSIA, CGI, ISAPI
General functionalities	Flickerless, heartbeat, mirror, privacy mask, watermark, IP address filtering, Anonymous access
Protocol	ONVIF(PROFILE S, PROFILE G), PSIA, CGI, ISAPI
Communication interface	1 RJ45 10 M / 100 M Ethernet interface
Reset Button	Yes
General	
Operating conditions	-30 °C ~ 60 °C humidity 95% or less (non-condensing)
Power supply	12 VDC ± 10% , PoE (802.3af)
Power consumption	Max. 5W (max. 7W with ICR switch)
Weather proof rating	IP66
IR range	20 to 30m
Dimension	60.4×76.9×139.28 mm
Weight	500g