

DynaHawk™ WH Series


Full HD Multiple Streams Micro Box IP Camera (WiFi / PoE)



The Full HD Multiple Streams Micro Box IP Camera is not only an easy setup camera, but a versatile solution for homes and small offices. For WiFi model, users can install the wireless IP camera in any place with Wi-Fi access. In addition, the both type of micro box camera has built-in microphone and speaker which allows two-way audio communication. For low light environments, the IP camera has incorporated Day/Night ICR technologies to capture clear images. 2 Megapixel resolution is supported for providing high definition images. Quad Streams Compression (H.264 Baseline / Main / High Profile + MJPEG) are available for efficient bandwidth and storage management. Users now can remotely and clearly watch over their families and homes via mobile devices while they are at work or even traveling.

■ Key Features

- Progressive Scan CMOS Sensor
- 2M Resolution
- Quad Streams Support
- Dual streams- Full HD 1080P + 720P Real-time
- Quad Streams Compression- H.264 Baseline / Main / High Profile + MJPEG
- Multi-language Support
- Wireless Network Support (WiFi model only)
- Wide Dynamic Range
- Built-In Microphone and Speaker*
- Motion Detection
- Privacy Masks
- Smart Picture Quality / 3D Noise Reduction
- Smart IR Mode
- Day/Night (ICR)
- IR LED Module (working distance up to 5 m)*
- microSD Support
- ONVIF Support



DynaHawk™ WH Series - Micro Box IP Camera

Camera		W1V1-H	W1S1-H
Image Sensor		1/2.7" Progressive CMOS	1/2.8" Progressive CMOS
Effective Pixels			1920(H) x 1080(V)
Minimum Illumination		0.2 lux (color)/ 0.02 lux (B/W) @30 IRE	
Shutter Speed		1 ~ 1/10000 sec.	
Lens			
Lens		Board lens	
Focal Length		2.8 mm / 3.6 mm	
F Number		F 2.0 / F 1.8	
FOV		105° / 87.6°	90.34° / 71.8°
Operation			
Multiple Languages	English / French / German / Italian / Japanese / Korean / Portuguese / Russian / Simplified Chinese / Spanish / Traditional Chinese		
Backlight Compensation	On / Off		
White Balance	Manual / AWB / ATW / One Push		
3D Noise Reduction	On / Off		
Wide Dynamic Range	On / Off		
Privacy Mask	On / Off		
Brightness	Manual		
Exposure	Auto / Manual		
Sharpness	Manual		
Contrast	Manual		
Saturation	Manual		
Hue	Manual		
Digital Zoom	Support		
Motion Detection	On / Off / By Schedule		
Privacy Mask Type	Color		
ICR	Auto / On / Off / Smart		
ICR+IR LED*	Auto / LED On / LED Off / Smart IR / Light Sensor		
Tampering Alarm	On / Off / By Schedule		
Two-way Audio	Embedded Mic in / Embedded Speaker Out*		
Audio Compression	G.711/G.726		
Network			
Interface	RJ-45, 10/100 Mbps Ethernet		
Video Compression	H.264 (MPEG-4 Part 10/AVC) / MJPEG		
Video Streaming	Dual Streams H.264 + MJPEG / H.264 + H.264 Quad Streams H.264*3 + MJPEG / H.264*4		
Video Resolution	H.264- Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF MJPEG- Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF		
Frame Rate	Single stream - 1080p (15/13 fps) Dual Streams - 1080p (15/13 fps) + 720p (30/25 fps)		
Protocol	ARP, IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF		
Security	PoE: HTTPS / IP Filter / IEEE 802.1X WiFi: HTTPS / IP Filter / IEEE 802.1X (WPA, WPA2)/Shared Key/Pair-wise Key		
Alarm	Input	1 Set 5V 10kΩ pull up	
	Output	1 Set Photo Relay Output 300V DC/AC	
Event Notification	HTTP / FTP / SMTP		
Micro SD	microSDHC 32GB support		
Supported Web Browser	Internet Explorer (6.0+) / Chrome / Firefox / Safari		
User Account	20		
Password Levels	User and Administrator		
Mechanical			
Built-in IR Illuminator*	Working Distance	up to 5 m	
	Wavelength	850 nm	
	Number of LEDs	2	
LED Indicator	PoE: Power / Link / ACT ; WiFi: Power (Green) / WiFi (Orange)		
Connectors	Alarm	4 Pin Terminal Block	
	Power	PoE: DC Jack / WiFi: Micro USB (with 1A USB charger)	
	Ethernet	PoE: RJ-45 ; WiFi: N/A	
General			
Operating Temperature	-10°C ~ 50°C (14° ~ 122° F)		
Humidity	10% ~ 90%, No Condensation		
Weatherproof Standard*	IP66		
Dimension	96.51 x 56 x 61.4 mm (3.78 x 2.2 x 2.42 in.)		
Weight	120g		
Power Source	PoE: DC 12V / PoE ; WiFi: 1A USB charger		
Power Consumption	WiFi: System 3 W (Built-in IR Illuminator: +0.8W) PoE: System 3.2 W (Built-in IR Illuminator: +1W)		WiFi: System 3.2 W (Built-in IR Illuminator: +0.8W) PoE: System 3.4 W (Built-in IR Illuminator: +1W)
Regulatory	CE / FCC		

* mark for optional items

Product specification and availability are subject to change without notice.



DYNACOLOR, INC.

No. 116, Jou Tz Street, Neihu, Taipei 114, Taiwan

TEL: (886)2-2659-8898

FAX: (886)2-2659-8868

http://www.dynacolor.com.tw

info@dynacolor.com.tw