

**Mini IP Bullet Camera**  
**ONL-52IR**
**OINONE**  
 your cctv choice


| Hardware                     |   |
|------------------------------|---|
| <b>Sensor</b>                | <b>1/3" Progressive Scan CMOS 1.3 MP</b>  |
| <b>Effective Pixels</b>      | 1280(H)×960(V)  |
| <b>Min.Illumination</b>      | 0.01Lux/F1.2(COLOR), 0.001Lux/F1.2(B/W), 0Lux(IR On)  |
| <b>Day/Night</b>             | Auto,dual IR-Cut filter, DWDR   |
| <b>IR LED</b>                | <b>12PCS Laser LED IR 60M</b>   |
| <b>Max S/N Ratio</b>         | 39dB  |
| <b>Electronic Shutter</b>    | Rolling Shutter   |
| <b>Lens</b>                  | <b>2.8-12mm Vari-Focal Lens</b>   |
| <b>Network Interface</b>     | 10/100M BASE-TX,RJ-45 connector   |
| <b>RS485</b>                 | Default as RS485 port for PTZ, 1ch Alarm input or 1ch alarm output optional                               |
| Audio video encoding         |   |
| <b>Video Compression</b>     | H.264 Main Profile;   |
| <b>Resolution</b>            | HD 960P (1280*960) 1-25fps  |
| <b>Sub Stream</b>            | CIF(352*288)/QVGA(320*240)/QCIF(176*144) 1-30fps  |
| <b>Video Bitrate</b>         | 32Kbps~4Mbps,Supports CBR/VBR   |
| <b>Privacy Mask</b>          | <b>4 configurable regions</b>   |
| <b>Auto Image Control</b>    | Auto Exposure Control (AEC); Auto White Balance (AWB); Auto Band Filter (ABF)                             |
| <b>Functions</b>             | Auto Black Level Calibration (ABLC)   |
| <b>Image Controls</b>        | Color saturation, hue, gamma, sharpness , lens correction, defective pixel canceling, and noise canceling |
| Data trans. & Storage        |   |
| <b>Data storage</b>          | Video and Image   |
| <b>Recording</b>             | Recording set up to record by motion trigger,alarm trigger, manual, or schedule                           |
| <b>Alarm Output</b>          | FTP,E-mail, Explorer, Software  |
| <b>Network protocol</b>      | TCP/IP、 UDP、 RTP、 RTSP、 RTCP、 HTTP、 DNS、 DDNS、 DHCP、 FTP、 NTP、 PPPOE、 SMTP、 UPNP                          |
| <b>ONVIF protocols</b>       | Support 1.02 version  |
| <b>Remote View</b>           | IE 6.0 or later, max 10 users   |
| General Parameters           |   |
| <b>Environmental Casing</b>  | <b>Waterproof (IP66 Rated), Outdoor Use</b>   |
| <b>Operating Temperature</b> | -20 °C ~ 50 °C (-4 °F ~ 122 °F) for DC 12V  |
| <b>Operating Humidity</b>    | 0% -85% RH  |
| <b>Power</b>                 | <b>PoE, DC12V 2.0A</b>  |
| <b>Power Consumption</b>     | 9 W(MAX)  |
| <b>Dimension</b>             | 268.7mmx108.4mmx89.9mm  |
| <b>Weight</b>                | 780g  |
| <b>Material</b>              | Aluminum Alloy  |

**Dimensions**
